

# Sandwich Board Sign A-Frame

Scan to view Product Instructional Video or visit:  
[www.creativedisplaysite.com/signicade.html](http://www.creativedisplaysite.com/signicade.html)



**Product Parts**

- 1 - Frame
- 2 - Ballast Plug
- 3 - Hook/Loop 12" (2 strips per panel)



## Sign Install

**A sign can be applied to both sides of your display by using any of the following methods:**

Adhesive-Backed Hook & Loop (Included)  
Well Nuts (Sold Separately)



Well Nut

## Display Setup

### Step 1

Use the handle to carry display to desired location. Pull the front and back of the folded Frame (1) apart to create an A-Frame that can stand on its own.



### Step 2

Pull the Ballast Plug (2) out to open the ballast fill hole. Fill with water or sand for ballast. Ballast can be added to both sides.



### Step 3

Affix included hook/loop (3) to back of graphic either at top/btm or side/side.

# Sandwich Board Sign A-Frame

## Graphic Install Using Well Nuts (Sold Separately - in pkgs of 20 Item #WN20)


### Step 1



Drill 6 - 1/2" holes into the frame in the desired location to attach the graphic. Insert the well nuts into the pre-drilled holes.



6 - Well Nuts with Screws





### Step 2

Screw bolt into well nut until it expands like a molly in drywall. Remove the screw and you now have a permanent screw receptacle enabling easy graphic replacement.

### Step 3

Position the sign on the frame to determine where holes need to be on the sign to line up with well nuts. Drill 1/4" holes in Sign for Bolt. Screw sign to frame(1).



## Storage

Store in a cool dry location.

## Care

To clean, wipe with damp cloth.